

Features	Specification	Panel	Downloads
----------	---------------	-------	-----------

Items	Specification
Voltage/Current	DC5V/1A
Power consumption	TX: 2W RX: <2W
HDMI compliance	HDMI1.3
HDCP compliance	HDCP1.4
HDMI resolution	720x576@50Hz, 720x480@60Hz, 1280x720@60Hz, 1920x1080@60Hz, 640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1280x800@60Hz, 1280x1024@60Hz, 1440x900@60Hz, 1680x1050@60Hz
Supports audio formats	PCM
Maximum transfer rate	10.2Gbps
Input and output TMDS signal	0.5~1.5Vp-p(TMDS)
Input and output DDC signal	5Vp-p(TTL)
Input cable length	≤8m(AWG24)
Output cable length	≤8m(AWG24)
Transmission length	CAT5: 80m CAT5E: 100m CAT6: 120m
Electrostatic protection of the whole machine	1a contact discharge level 3, 1b air discharge level 3, implementation of the standard: IEC61000-4-2
Working temperature	0~60℃
Storage temperature	-10~70℃
Humidity (no condensation)	0~90%
Dimension	69.57(L) x 58.80(W) x 16.10(H)mm

Material	Aluminium alloy material + crystal panel
Treatment process	Grit blast
Color	Black
Weight	TX:70g, RX:70g

Product

New Product

HDMI over IP

Modular Matrix

Video Wall Controller

Multiview & Switch

News

Product News

Company News

Souports

FAQ

Download

Technical

About Us

Company Overview

R&D Capability

Sales Market

Certifications

Contanct Us

Tel:+86 755 83593885

Email:sales@lenkeng.net

News Subscribe:

submit

