

# Fluke 101 Digital Multimeter

The FIRST-CHOICE multimeter for electrical professionals



### **Technical Data**

Designed for basic electrical tests, the Fluke 101 digital multimeter offers reliable measurements for residential/ commercial electricians and heating and air conditioning technicians. This small, lightweight multimeter fits comfortably in your hand but is rugged enough to withstand daily use for years to come. When it comes to professional-grade affordable multimeters, the Fluke 101 digital multimeter is your best choice.

## Fluke 101 Product Highlights

- Basic dc accuracy 0.5 %
- CAT III 600 V safety rated
- Diode and continuity test with buzzer
- Small lightweight design for one-handed use
- Rugged, durable design
- Automatic shutdown
- Battery is easy to replace



#### **Specifications**

#### **Electrical specifications**

Function	Range	Resolution	Accuracy
AC volts (40 Hz to 500 Hz)	600.0 mV 6.000 V 60.00 V 600.0 V	0.1 mV 0.001 V 0.01 V 0.1 V	3.0 % ± 3 digit 1.0 % ± 3 digit
DC volts	6.000 V 60.00 V 600.0 V	0.001 V 0.01 V 0.1 V	0.5 % ± 3 digit
Resistance ohms	400.0 Ω 4.000 kΩ 40.00 kΩ 400.0 kΩ 4.000 MΩ 40.00 MΩ	0.1 Ω 0.001 k Ω 0.01 k Ω 0.1 k Ω 0.001 M Ω 0.01 M Ω	0.5 % ± 3 digit 0.5 % ± 2 digit 0.5 % ± 2 digit 0.5 % ± 2 digit 0.5 % ± 2 digit 1.5 % ± 3 digit
Capacitance	50.00 nF 500.0 nF 5.000 μF 50.00 μF 100.0 μF	0.01 nF 0.1 nF 0.001 μF 0.01 μF 0.1 μF	NA
Frequency (10 Hz to 100 kHz)	50.00 Hz 500.0 Hz 5.000 kHz 50.00 kHz 100.0 kHz	0.01 Hz 0.1 Hz 0.001 kHz 0.01 kHz 0.1 kHz	NA
Duty cycle	0.1 % to 99.9 %	0.1%	NA

#### **General specifications**

Continuity (audible)	Yes	
CAT rating	CAT III 600 V	
Auto shutoff	Yes	
Size (HxWxL)	130 mm x 65 mm x 27mm	
Weight	160 g	
Battery	Two AAA	
Warranty	1 year	
IP rating	IP 40 per IEC 60529	
Drop test	1 meter to surface	
Temperature	Operating: 0 °C to 40 °C	
	Storage: -30 °C to 60 °C	

## **Ordering information**

FLUKE-101 Digital Multimeter

#### **Included equipment**

- TL75 Test leads
- 2 AAA Batteries (installed)



Fluke. The Most Trusted Tools in the World.

**Fluke Corporation** 

PO Box 9090, Everett, WA 98206 U.S.A.

Fluke Europe B.V.

PO Box 1186, 5602 BD Eindhoven, The Netherlands

For more information call:

In the U.S.A. (800) 443-5853 or Fax (425) 446-5116 In Europe/M-East/Africa +31 (0) 40 2675 200 or Fax +31 (0) 40 2675 222 In Canada (800)-36-FLUKE or Fax (905) 890-6866 From other countries +1 (425) 446-5500 or Fax +1 (425) 446-5116 Web access: http://www.fluke.com

©2013 Fluke Corporation. Specifications subject to change without notice. Printed in U.S.A. 7/2013 6000031A\_EN

Modification of this document is not permitted without written permission from Fluke Corporation.